

HSL PDUI - JUNCTION BOX

The PDUI is a 12/24 output power supply that powers 12V DC powered devices such as HSL's isolators. The PDUI can supply a maximum of 1.5A of current to each of the 12/24 devices. The PDUI solves lack of space and power outlets problem for crowded installations, by eliminating the need for many 12V DC power adapters.

With two power inlets for redundancy, the PDUI is a rigid and robust solution for mission-critical installations.



SPECIFICATION

PART NUMBER	PDUI12	PDUI24
PDUI FEATURES		
AC 100-240 inputs	2	2
DC 12v Power outputs	12	24
PHYSICAL		
Dimensions	342x148x42 mm / 13.7x5.8x1.7 inches	
ENVIRONMENTAL		
Operating Temperature	32° to 104° F (0° to 40° C)	
Storage Temperature	-4° to 140° F (-20° to 60° C)	
Humidity	0-80% RH, non-condensing	
GENERAL INFO		
Made In	ISRAEL	
Product life-cycle	10 years	
Warranty	2 Years	

ACCESSORIES:

MODEL	DESCRIPTION	P/N
PDUI1.5	1.5M DC Junction box cable	CMA20843
PDUI2	2M DC Junction box cable	CMA20868
PDUI4	4M DC Junction box cable	CMA20196

SUPPORTS HSL'S MODELS:

ISOLATOR MODEL	P/N
FI11D-M	CPN14753
FV11D-M	CPN14750
FI11P-M	CPN14754
FV11P-M	CPN14751
FI11H-M	CPN14755
FV11H-M	CPN14752

