

# THUNDERBOLT DUAL DP DRIVERLESS DOCKING STATION



THUNDERBOLT CONNECTOR

High Sec Lab's TAA/BAA compliant Thunderbolt 3.0 Docking Station connects multiple peripheral devices to a host computer using a single high-performance Thunderbolt port. 100W of power delivery along with 1Gbps LAN augment the peripheral device connectivity. Use the UK12PHT-N to leverage the flexibility of Thunderbolt to easily connect peripherals to a host computer, or to connect a computer source to an HSL KVM switching device.



## THUNDERBOLT DOCKING STATION HIGHLIGHTS

- Made in the USA**  
 TAA and BAA compliance assuring the highest supply chain security and quality.
- Fully Compatible**  
 Supports USB 3.0. Compatible with both Thunderbolt 3.0 and USB-C.
- Driverless, Thunderbolt Connectivity with 100W Power Delivery (PD 3.0)**  
 No driver installation required to access 100W Power Delivery (PD 3.0) provided by the power supply included with the product. The best docking station for Windows OS laptops having a Thunderbolt port that supports DisplayPort Alt Mode and Power Delivery.
- Dual Head Video Ports**  
 With two DisplayPort video ports, the user has full flexibility in using primary and extended monitors. Resolutions supported vary by the device connected but are up to 4K 60HZ for both single and dual head connections.
- Rugged Design for Easy of Installation**  
 Especially designed for under the desk mounting. Rack mounts available.

## SPECIFICATION

MODEL NUMBER	UK12PHT-N
<b>FEATURES</b>	
<b>Input Interface (Host)</b>	LAN + Thunderbolt 3.0
<b>Output Interface (Console)</b>	DP Dual head 4K60Hz
<b>USB Compliance</b>	4 x Type A: 2 x USB 3.0, 2 x USB 2.0
<b>Charging</b>	PD 3.0 compliant up to 100W with the supplied charger
<b>PHYSICAL</b>	
<b>Dimensions</b>	145 x 105 x 28 mm / 5.8 x 4.2 x 1.1 inches
<b>Weight</b>	0.3 kg (0.64 lbs)
<b>ENVIRONMENTAL</b>	
<b>Operating Temperature</b>	-0°C to 40°C (32°F to 104°F)
<b>Storage Temperature</b>	-20°C to 60°C (-4°F to 140°F)
<b>Humidity</b>	Operating: 20% to 80% RH non-condensing Storage: 10% to 90% RH non-condensing
<b>Altitude</b>	0 to 10,000 ft
<b>GENERAL INFO</b>	
<b>Made In</b>	ISRAEL/USA
<b>Product Life-cycle</b>	10 years
<b>Warranty</b>	2 Years

Thunderbolt Docking Station System Diagram

